

# Water softeners

## Watermark Installation example Domestic water softener Watermark-30



### Private garage installation

Description	Code
1. Watermark 30 softener	795211
2. Filtermax pre-filter	723619
3. Sample intake valve	265000
4. Drainage	-
5. 1" Flexible hose	718601
6. Starfit 22 mm quick-connector bypass set	656805
7. Power supply 220 V	960016

## Denver Plus Installation example Domestic water softener Denver Plus 30



### Laundry room installation

Description	Code
1. Denver Plus 30 Softener	762917
2. Filtermax pre-filter	723619
3. Sample intake valve	265000
4. Drainage	-
5. 1" Flexible hose	718601
6. Starfit 22 mm quick-connector bypass set	656805
7. Power supply 220 V	960016

# Denver Plus

## Denver Plus slim high efficiency compact water softeners



### Description

This is the slimmest water softener in the market, with a width of only 20 cm. Cabinet provided with a sliding brine tank cover and electronic controller.

New generation system with an easy-to-program metered valve.

System is composed by a GRP bottle with top and bottom distributors and polyethylene cabinet.

WS180-HE valve, electronic programmed, delayed regeneration with day override.

Brine valve included in the cabinet.

Isolation by-pass and hardness mixer included.

### Specifications

Min. pressure: 2.5 kg/cm<sup>2</sup>.

Max. pressure: 8.5 kg/cm<sup>2</sup>.

Min. temperature: 4 °C.

Max. temperature: 35 °C.


Power supply: 220 Vac/50 Hz, other voltages available under request.

! Do not forget to order flexible metal hoses, Code 718602 (3/4")

Code	Description	Resin volume L	Connection	Exchange capacity °HFxm <sup>3</sup>	Salt consumption kg	Working flow m <sup>3</sup> /h	Peak flow m <sup>3</sup> /h	Packaging units
762921	Denver Plus Slim 6	6	3/4"	14 22,6	0,36 0,72	0,3	0,4	1
762926	Denver Plus Slim 12	12	3/4"	31 48 55	0,72 1,44 1,92	0,5	0,8	1
762923	Denver Plus Slim 15	15	3/4"	42 65 75	0,9 1,8 2,4	0,6	1	1



Code	A	B	C
762921	465	200	360
762926	700	200	360
762923	1025	200	360
			<b>mm</b>



Code	Description	Packaging units
900601	1" male elbow adapter	1
900600	3/4" male elbow adapter	1

## Denver Plus wide high efficiency compact water softeners



### Description

New generation water softener system with an elegant cabinet provided with a sliding brine tank cover and electronic controller.

It includes an easy-to-program metered valve. System is composed by a GRP bottle with top and bottom distributors and polyethylene cabinet.

WS180-HE valve, electronic programmed, delayed regeneration with day override.

Noryl male connection (size depending on model).

Brine valve included in the cabinet.

Isolation by-pass and hardness mixer included.

### Specifications

Min. pressure: 2.5 kg/cm<sup>2</sup>.

Max. pressure: 8.5 kg/cm<sup>2</sup>.

Min. temperature: 4 °C.

Max. temperature: 35 °C.


Power supply: 220 Vac/50 Hz, other voltages available under request.

! Do not forget to order flexible metal hoses, Code 718601 (1") 718602 (3/4")

Code	Description	Resin volume L	Connection	Exchange capacity °HFxm <sup>3</sup>	Salt consumption kg	Working flow m <sup>3</sup> /h	Peak flow m <sup>3</sup> /h	Packaging units
762916	Denver Plus 12,5	12,5	3/4"	31 48 55	0,8 1,5 1,92	0,5	0,8	1
762945	Denver Plus 18	18	1"	57 82 119	1,1 2,2 4,5	0,8	1,1	1
762917	Denver Plus 30	30	1"	115 170 210	1,8 3,6 7,5	1,2	1,8	1



Code	A	B	C
762916	575	333	505
762945	1034	333	505
762917	1034	333	505
			<b>mm</b>



Code	Description	Packaging units
900601	1" male elbow adapter	1
900600	3/4" male elbow adapter	1